

Poster presentation

Open Access

## Influence of prior expectations on contour integration: psychophysics and modeling

Marc Schipper\*<sup>1</sup>, Udo Ernst<sup>2</sup>, Klaus Pawelzik<sup>2</sup> and Manfred Fahle<sup>1</sup>

Address: <sup>1</sup>Department for Human Neurobiology, Institute for Brain Research, Bremen University, Bremen, Germany and <sup>2</sup>Department for Neurophysics, Institute for Theoretical Physics, Bremen University, Bremen, Germany

Email: Marc Schipper\* - marc.schipper@uni-bremen.de

\* Corresponding author

from Eighteenth Annual Computational Neuroscience Meeting: CNS\*2009  
Berlin, Germany. 18–23 July 2009

Published: 13 July 2009

BMC Neuroscience 2009, **10**(Suppl 1):P12 doi:10.1186/1471-2202-10-S1-P12

This abstract is available from: <http://www.biomedcentral.com/1471-2202/10/S1/P12>

© 2009 Schipper et al; licensee BioMed Central Ltd.

Contour integration is a process linking oriented and colinearly aligned edge elements into coherent percepts. This process is thought to rely predominantly on feedforward and recurrent integration mechanisms, making its percepts very salient ("pop-out") and independent of top-down processes. However, recent studies have shown that attention can strongly modulate contour integration, suggesting the importance of the confluence of bottom-up (sensory input) and top-down (prior expectations) processes for this task. To uncover neural substrates and mechanisms underlying the influence of prior expectations on contour integration, we combine psychophysical with modeling studies. Participants had to carry out two experiments with identical visual stimuli but different behavioural tasks: a detection task (A) and a discrimination task (B). Stimuli consisted of vertical and horizontal ellipses formed by aligned Gabor elements, being embedded in a Gabor field with random orientations and positions. Each visual hemifield could contain one of a vertical, a horizontal or no ellipse. All combinations of these three basic configurations were possible, totalling to nine stimulus categories for the two hemifields. In experiment A, participants had to give a yes response whenever one stimulus contained at least one ellipse (contour); in experiment B only when a target was present (this target could be either a horizontal or a vertical ellipse, in any hemifield of the stimulus).

In the detection task, reaction times (RT) for horizontal ellipses are ~70 ms shorter than for vertical ellipses. In the

discrimination task, RTs for targets are consistently shorter than for distractors, even if the bias for horizontal ellipses is taken into consideration. The presence of redundant targets (e.g. two horizontal ellipses instead of only one horizontal ellipse) also shortens RTs. Thus, the psychophysical data clearly demonstrate a pronounced influence of higher cognitive processes on contour integration.

In our contour integration model [1], we explore the hypothesis that top-down influences directly modulate the response characteristics of elementary feature detectors [2]. We first assume that the prevalence of horizontal lines in natural images leads to an increased activation of horizontal feature detectors. In a discrimination task, we provide a second bias either to horizontal or vertical feature detectors. When presenting a stimulus from the nine possible categories, any existing contour is integrated by the model and leads to a higher activation of edge detectors stimulated by contour elements. The mean amplitude of this activation is determined by the balance between the two different biases. In conjunction with fixed thresholds for contour detection and discrimination, these dynamics yield RTs that not only depend on the exact stimulus, but also on the top-down priming. The simulated RTs are in good qualitative agreement with our psychophysical experiments. We conclude that feature integration may serve as a mechanism to convert priors on single features into preferences for global Gestalt properties.

## Acknowledgements

This work has been supported by the BMBF as a part of the National Bernstein Network for Computational Neuroscience (Bernstein Group Bremen), and by the Zentrum für Kognitionswissenschaften (ZKW) Bremen.

## References

1. Schinkel N, Pawelzik KR, Ernst UA: **Robust integration and detection of noisy contours in a probabilistic neural model.** *Neurocomputing* 2005, **65-66C**:211-217.
2. McAdams CJ, Maunsell JHR: **Attention to both space and feature modulates neuronal responses in macaque area V4.** *J Neurophys* 2000, **83**:1751-1755.

Publish with **BioMed Central** and every scientist can read your work free of charge

*"BioMed Central will be the most significant development for disseminating the results of biomedical research in our lifetime."*

Sir Paul Nurse, Cancer Research UK

Your research papers will be:

- available free of charge to the entire biomedical community
- peer reviewed and published immediately upon acceptance
- cited in PubMed and archived on PubMed Central
- yours — you keep the copyright

Submit your manuscript here:  
[http://www.biomedcentral.com/info/publishing\\_adv.asp](http://www.biomedcentral.com/info/publishing_adv.asp)

